

Manhole Covers Ireland

We cover everything!

<u>Portland, Lorrha, Nenagh, Co. Tipperary E45 DH99.</u> Phone 094 9033 022 Fax 094 925 4970

Email: info@mhcireland.com Website www.mhcireland.com

430 x 370 D400 Locked Grating and 100H Frame



Inspection manhole cover in Spheroidal cast iron with load bearing capacity over 400 kN + 10% (40 tons), conforming to the load class D400 as set out by norm EN 124-2 2015

Product Code	Overall Size	Clear Opening	Frame Height	Waterway Area	3rd Party Certification
MH-GF-D-4337-LKD	584 x 458mm	434 x 374mm	100mm	1080cm2	BSI KITEMARK

Manufactures Name = ISTIKAMET
Manufactures Code = ID2218

Features: - 3rd Party Certified to BS EN124-2 2015 (copy certificate available upon request)

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:2012. Bitumen-based paint coating to BS

3416.

Basic Dimensions: MH-GF-D-4337-LKD **Clear Opening** = 434mm x 374mm

Overall size = 584mm x 458mm Depth = 100mm

Waterway Area: = 1080cm2

Load Rating Classification: D400 (40 tonnes) - Captive hinge design to deter thieves

- 3-Sided Flange for installation against kerbs
- "Taper-Lock" Grating design to ensure non-rocking
- Can be reversed Hinged

Intended Use:

Group 4 – minimum Class D400. For use in areas where cars and lorries have access, including carriageways, hard shoulders and pedestrian areas. (See norm EN 124 group 4). THE CHOICE OF THE CORRESPONDENT PRODUCT IS PART OF THE RESPONSIBILITY OF THE PROJECT ENGINEER. The National Roads Authority Design Manual for Roads and Bridges also recommends the use of class E600 for large traffic volumes (in excess of 1,500 vehicles) per day on national roads. IF IN DOUBT, WE SUGGEST TO CHOOSE THE SUPERIOR CLASS OF PRODUCTS.