



Manhole Covers Ireland

We cover everything!

Lowpark, Charlestown, Co. Mayo, Ireland.

Phone 094 9033 022 Fax 094 9254970

Email: info@mhcireland.com web Site www.mhcireland.com

Istanbul Side Entry Kerb C250 Gully

Istanbul Side Inlet Kerb Gully



Group 3

For gullies installed in kerbside channels of the pavement which, extends to 0.5 m in the road and to 0.2 m top on the pavement, when measured from the edge.

EN124-2 C250

Product Code	Length	Width	Opening	Height	Load Class
MH-KG-M1151	900mm	900mm	700 x 700mm	206mm	C250

It is made as a single cast, which facilitates its installation and reduces the unit load on the supporting wall. It is particularly tall, which means it can be used in any type of Kerb Line. It has finger bars on the front, which allow the inlet of water and avoids the introduction of any rubbish (stones, leaves and cans). The cover is hinged which allows for the easy access. The upper side, which can be walked on, presents anti-skip grips. The new pavement inlet solves all the problems of highway drainage thanks to drains gratings: for example, when the vertical grating is blocked due to the presence of rubbish, leaves or other, when the asphalt embankment tends to reduce the rise of the pavement, or in case of accidental alterations of the road section. This model, totally new, facilitates any action of workmen to free the inlet from surface obstructions.

- Manufactured to BS EN 124 class C 250 as specified
- 3rd Party assurance of quality
- Suitable for carriageway applications
- Captive hinged for easy access and increased security (kerb drainage units)
- Non-rock captive hinged for stability and silent operation
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish