Manhole Covers Ireland We cover everything! Portland, Lorrha, Nenagh, Co. Tipperary E45 DH99. Phone 094 9033 0222 Fax 094 925 4970 Email: info@mhcireland.com Website: www.mhcireland.com D400 Moscow Double Tri Cover & 150H Frame



Inspection manhole cover in Spheroidal cast

iron EN- GJS-500-7 with load bearing capacity over 400 kN (40 tons), conforming to the load class D400 as set out by norm EN 124-2 2015.

Optional Extra's





Product Code	Overall Size	Clear Opening	Frame Height	Waterway Area	3rd Party Certified
MH-D-3030-15	400 x 400mm	300 x 300mm	150mm	N/A	Yes
MH-D-4545-15	550 x 550mm	450 x 450mm	150mm	N/A	Yes
MH-D-6767-15	827 x 827mm	675 x 675mm	150mm	N/A	Yes
MH-D-6060-15	750 x 750mm	600 x 600mm	150mm	N/A	Yes
MH-D-7560-15	915 x 765mm	750 x 600mm	150mm	N/A	Yes
MH-D-7575-15	904 x 904mm	750 x 750mm	150mm	N/A	Yes
MH-D-9060-15	1054 x 754mm	900 x 600mm	150mm	N/A	Yes
MH-D-12067-15	1374 x 850mm	1200 x 675mm	150mm	N/A	Yes
MH-D-9090-15	1050 x 1050mm	900 x 900mm	150mm	N/A	Yes

Sub-Category: D400 Multi-Tri Manhole Covers for use in highways and commercial/industrial areas.

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7. Temporary Bitumen-based paint coating to BS 3416.

Load Rating Classification: D400 (40 tonnes)

Frame Height: 150mm

Features: - 3rd Party Certified to BS EN124-2 2015

(copy certificate available upon request)

- Non-rock 3 point suspension covers
- Integral lifting key holes (to suit CLKS 552 lifting keys, available separately).
- Optional 'locking' version (ask for details)
- Any badging available on Request.
- Compliant with Design Requirements of HA104/02
- The covers are interchangeable, the upper surface is designed to be antiskid to EN124-1:2012,8.4, to allow the complete flow of runoff water and avoid the creation of ice.